

## HYDRAULIC MOTOR DRIVE



- ⊘ Most durable and reliable scissor stacks
- ⊘ Reinforced working platform
- ⊘ Advanced charger with voltage protection
- ⊘ Higher driver comfort and security

## PRODUCT SPECIFICATION

Model	AS0607	AS0607W	AS0608	AS0808	AS1012	AS1212	AS1412
Lift Capacity	230kg	230kg	380kg	230kg	320kg	320kg	>10m 200kg <10m 320kg
Lift Capacity Extension	120kg	120kg	113kg	113kg	113kg	113kg	113 kg
Max. Platform Occupants	2	2	2	2	2	2	2
Max. Working Height(A+2)	7,8m	7,8m	7,9m	10m	12m	14m	15,8 m
Overall Length(B)	1,83m	1,83m	2,47m	2,47m	2,47m	2,47m	2,68m/2,79m
Overall Width(C)	0,76m	0,81m	0,83m	0,83m	1,18m	1,18m	1,25m
Overall Height-Rails Fokied(D)	/	/	1,84m	1,96m	1,8m	1,96m	2,1m
Platform Extension Length	0,9m	0,9m	0,9m	0,9m	0,9m	0,9m	0,9m
Driving Speed(stowed/raised)	4/0,8km/h	4/0,8km/h	3,5/0,8km/h	3,5/0,8km/h	3,5/0,8km/h	3,1/0,8km/h	3,5/0,8km/h
Up/Down Speed-GB	16/34sec	16/34sec	34/34sec	31/40sec	62/39sec	65/60sec	80/60sec
Up/Down Speed-CE	16/34sec	16/29sec	30/34sec	31/40sec	62/74sec	65/60sec	/
Gradeability	25%	25%	30%	25%	25%	25%	25%
Max. Slope	1,5°/3°	1,5°/3°	1,5°/3°	1,5°/3°	2°/3°	1,5°/3°	1,5°/3°
Machine Weigh	1560kg	1570kg	2050kg	2180kg	3000kg	3300kg	3300kg

